

**ATTRACTION**<sup>®</sup> is a semi-flexible tile constructed by compacting, at high temperature and over **3000 T**, a **4mm** recycled backing and a **1mm** pure vinyl wear layer. This wear layer is incorporating very densely pressed coloured chips, with a mat finishing and without a transparent wear layer.

The product comprises a compact backing which is pressed and reinforced with two glass fibre grids.

**ATTRACTION**<sup>®</sup> has a unique dovetail joint which allows fast loose lay installation and replacement.

**ATTRACTION**<sup>®</sup> is treated with **Protecsol**<sup>®2</sup>, a surface treatment obtained by **UV** laser crosslinking. This **Protecsol**<sup>®2</sup> ensures easy maintenance and eliminates permanently the need for acrylic emulsion (metallisation). It avoids staining of chemical products used in healthcare like iodine alcohol, Betadine, eosin and anti-bacterial hand gel.

It has a **Bfl-s1** fire classification in accordance with standard **EN 13501-1**.

The products emission rate of volatile organic compounds is **<10µg/m<sup>3</sup> (TVOC after 28 days – ISO 16000-6)**. It is made of **100%** controlled recycled materials. It does not contain any heavy metals or **CMR 1&2** and they are **100%** compliant with **REACH**.

**ATTRACTION**<sup>®</sup> is **100% recyclable** and made with up to **80% recycled content**.