

<b>DESCRIPTION</b>			
Total thickness	ISO 24346 (EN 428)	mm	5
Wearlayer thickness	ISO 24340 (EN 429)	mm	1
Weight	ISO 23997 (EN 430)	g/m <sup>2</sup>	7460
Tile size	ISO 24342 (EN 427)	mm	635 x 635 Connect 600 x 600 Cleantech (without dovetail)
<b>CLASSIFICATION</b>			
Norm / Product specification	-	-	ISO 10582 (EN 649)
European classification	ISO 10874 (EN 685)	class	34 - 43
Fire rating	EN 13501 - 1	class	Bfl-s1
Static electrical propensity	EN 1815	kV	< 2
Slip resistance wet	DIN 51 130	class	R10
<b>PERFORMANCES</b>			
Type binder content	ISO 10582	type	I
Dimensional stability	ISO 23999 (EN 434)	%	≤ 0.25
Residual indentation	ISO 24343-1 (EN 433)	mm	≤ 0.10
Castor chair test	ISO 4918 (EN 425)	-	OK
Thermal conductivity	ISO 10456 (EN 12524)	W/(m.k)	≈ 0.25
Colour fastness	ISO 105 - B02	degree	≥ 6
Chemical products resistance	ISO 26987 (EN 423)	-	OK
Surface treatment	-	-	ProtecSol®2
<b>ENVIRONMENT / INDOOR AIR QUALITY</b>			
TVOC after 28 days	ISO 16000 - 6	µg/m <sup>3</sup>	< 10
Certification	-	-	Floorscore®
<b>CE MARKING</b>			
	<b>EN 14041</b>	  	
			