

**DESCRIPTION**

Total thickness	ISO 24346 (EN 428)	mm	2
Weight	ISO 23997 (EN 430)	g/m <sup>2</sup>	3060
Width of sheet	ISO 24341 (EN 426)	cm	200
Length of sheet	ISO 24341 (EN 426)	ml	20

**CLASSIFICATION**

Norm / Product specification	-	-	ISO 10581
European classification	ISO 10874 (EN 685)	class	34 - 43
Fire rating	EN 13501-1	class	Bfl-s1
Static electrical propensity	EN 1815	KV	<2
	IEC 61340-4-5	V	< 100
Electrical resistance	EN 1081	Ω	$10^4 \leq R_t \leq 10^6$
Slip resistance wet	DIN 51130	class	R9






**PERFORMANCES**

Type binder content	ISO 10581	type	I
Dimensional stability	ISO 23999 (EN 434)	%	≤ 0.40
Thermal conductivity	ISO 10456 (EN 12524)	W/(m.K)	0.25
Colour fastness	ISO 105 - B02	degree	≥ 6
Chemical products resistance	ISO 26987 (EN 423)	-	OK
Anti-bacterial activity (E. coli - S. aureus - MRSA) <sup>(1)</sup>	ISO 22196	-	>99% Inhibits growth
Color number	-	-	6
Surface treatment	-	-	Evercare
Antiviral activity (human coronavirus 229E)	ISO 21702		99.7% after 2h

**ENVIRONMENT / INDOOR AIR QUALITY**

TVOC after 28 days	ISO 16000 - 6	µg/m <sup>3</sup>	< 10
Certification	-	-	Floorscore®

**CE MARKING**

	EN 14041	   
--	----------	---

(1) The implementation of an effective cleaning regime is the most important defence against infections.